

# **RTEX REWRITES THE PROFITABILITY RULEBOOK**

Reducing energy consumption  
by 50 % whilst being 25 %  
lighter paired with great  
ergonomics.

*Atlas Copco*



  
INDUSTRIE  
PREIS 2016  
BEST OF

# RTEX THE HARD FACTS

Pneumatic breaker		RTEX	RTEX
Weight	kg	25	25
Length	mm	780 / 685 (notched chisel)	780
Air consumption	l/s	17,5	18
Impact rate	blows/min	845	870
Vibration level 3 axes (ISO 28927-10) <sup>1)</sup>	m/s <sup>2</sup>	5	4.8
Vibration level 3 axes (spreads) <sup>1)</sup>	m/s <sup>2</sup>	1.0	1.0
Sound power level guaranteed (2000/14/EC) <sup>1)</sup>	Lw, dB(A)	107	107
Measured power level guaranteed (2000/14/EC) <sup>1)</sup>	Lw, dB(A)	101	101
Sound pressure level (ISO 11203) <sup>1)</sup>	Lp, r=1m	90	90
Pressure max	bar	7	7
Shank size: Hex	mm	28x152 / 28x160 / 28 notch	32x152 / 32x160
Harmonised standard applied		EN ISO 11148-4:2012	EN ISO 11148-4:2012
Part number	mm	8461 0125 20	8461 0125 30

<sup>1)</sup> Important: Full details of measurement are available in the Safety and Operating Instruction of the product (part no 9800 1724 71). It can be found on [www.acprintshop.com](http://www.acprintshop.com)

Download a QR reader and scan the codes to watch the videos.



RTEX breaker comparison



Atlas Copco RTEX

## COMMITTED TO SUSTAINABLE PRODUCTIVITY

We stand by our responsibilities towards our customers,  
towards the environment and the people around us.  
We make performance stand the test of time.  
This is what we call – Sustainable Productivity.

[www.atlascopco.com](http://www.atlascopco.com)

Atlas Copco