John Deere HPX815E Work Series Utility Vehicle

ENGINE		
Туре	3 cyl, 4-cycle diesel	
Displacement	854 cc	
Power	13.57* kW18.2 hp	
Cooling system	Liquid	
DRIVETRAIN		
Transmission	Continuously Variable Transmission (CVT)	
Final drive	Two speed, oil bath	
Four wheel drive	Yes	
Traction assist	Positive locking, mechanically actuated (hand-operated)	
Descent control	No	
Maximum traveling speed	0-25 mph (0-40 km/h) forward0-12 mph (0-19 km/h) reverse	
SUSPENSION		
Front	Independent with McPherson Strut	
Rear	Coil over shock	
BRAKES		
Туре	Hydraulic Disc brakes	
Park brake	Rear mechanical disk, hand operated	
TIRES / WHEELS		
Front	24 x 9.5-10	
Rear	24 x 12.0-10	
DIMENSIONS / CAPACITIES		
Wheelbase	1910 mm75.2 in.	
Dry weight	681 kg1526 lb	
Length	2743 mm108 in.	
Width	1506 mm59.3 in.	
Height	1867 mm73.5 in.	
Tread centers	Front: 1257.3 mmFront: 49.5 in.Rear: 1219.3 mmRear: 48 in.	
Ground clearance	152.4 mm6.0 in.	
Fuel capacity	20.1 L5.3 U.S. gal.	

Cargo box dimensions	1143 x 304.8 x 1320 mm45 x 12 x 52 in.
Cargo box capacity (weight)	454 kg1000 lb
Payload capacity	635 kg1400 lb
Towing capacity	590 kg1300 lb
Hitch	Standard 2-in receiver
FEATURES	
Color	Green/Yellow
Power steering	No
Battery / Alternator / Power port	480 CCA 40 amp @ 3200 rpm
Instrumentation	
Storage	Cup Holders, Glove box
Seating	Bucket Seats (Bench Available)
Headlights	Halogen
ADDITIONAL INFORMATION	
Country of Manufacture	U.S.
Date collected	