



## VIBRATORY PLATES CF / CFR

Paver Roller

Vibratory Plates

Soil Compactors

Vibratory Rammers

Duplex/Trench Rollers

Concrete-/  
Cutting Technologie

Benefits



The vibratory plate compactors of the CF 2 and CF 3 series distinguish themselves by premium operating comfort, compact dimensions and optimum running characteristics. Their fields of application: compaction work in landscaping and repair work.

The special low-vibration guide bar (CF 2 and CF 3) reduces the hand/arm vibrations and ensures comfortable work. In addition, the guide bar features a soft, user-friendly plastic coating.

The CF 2 A was specially designed for asphalt compaction.

The CFR 90 is an alternative to the „standard“ vibratory plates. The almost round base plate allows for high maneuverability in confined areas, for example in cable trenches or along curbs.







CF 2 Hd

Picture with  
accessories

CF 2 A



### AVAILABLE ACCESSORIES

- Integrated wheel kit.
- Water sprinkler system (for asphalt compaction).
- Polyurethane pad.

Picture with  
accessories

CF 3

Typ	CF 2 Hd	CF 2 A	CF 3 Hd / CF 3 / 60 Hd	CF 3 / CF 3 / 60
Operating weight CECE, kg	84	82	96 / 107	111 / 122
Working width, cm	45	45	50 / 60	50 / 60
Centrifugal force, kN	15	15	20	20
Frequency, Hz	95	95	95	95
Engine	Honda GX 160 4-stroke, gasoline	Honda GX 160 4-stroke, gasoline	Honda GX 160 4-stroke, gasoline	Hatz 1B20 Diesel
Engine output, max. kW (HP)	3.6 (4.9)	3.6 (4.9)	3.6 (4.9)	3.5 (4.8)
Power output at operating speed	2.7 (3.7) at 3,000 kW (HP) at r.p.m.	2.7 (3.7) at 3,000 kW (HP) at r.p.m.	2.7 (3.7) at 3,000 kW (HP) at r.p.m.	3.1 (4.2) at 3,000 kW (HP) at r.p.m.
Working speed, m/min	26	26	26	24
Dimensions (L x W x H), cm	113 x 45 x 96	113 x 45 x 96	116 x 50/60 x 96	116 x 50/60 x 106