

Specification Data Sheet | Model: 200TTCABIMDG



TRANSTANK CONTAINER 18,500 Litre

TransTank Container, 110% bunded (double wall), ISO fuel tank container, ADR ch.6.7, CSC, IMDG (IMO), RID, UIC, UN, USDot, TIR Approved for transport and UL142 and ULC-S601 for storage of diesel fuel.

- ◆ ISO container approved to transport fuel on the road, rail & sea.
- ◆ To comply with environmental regulations for fuel storage, outer tank bund is 110% capacity of inner tank. To help prevent leakage of fuel through joints, there are no bottom outlets in accordance with PPG2 Regulations.
- ◆ Sized to ISO container specifications for economical transport, storage & logistics worldwide. Can also be stacked 6 high full of fuel reducing transport & storage space requirements.
- ◆ CSC plated (made to Convention for Safe Container Standard), fully framed unit with corner twist locks to facilitate transport & lifting of tank.
- ◆ Vessel – Inner tank pressure tested to 4 Bar. Material suitable for use down to -40°C.
- ◆ Pressed heavy steel exterior plates for additional strength.
- ◆ All valves, outlets, hoses & pump housed within lockable weatherproof cabinet.
- ◆ Fast fill fuel pipe & high quality tank contents gauge.
- ◆ Connections & pump housed in bunded area for extra environmental protection.
- ◆ Large storage cabinet with drip sump, shelves & ability to house high volume diesel engine pump.
- ◆ Internal baffles to prevent fuel surge & provide safe handling & transportation at any fill level.
- ◆ Option for 4 sets of feed & return connections, plus pump/auxiliary equipment feed. For additional security, hoses can be fed through access holes enabling doors to be kept locked whilst in use.
- ◆ Inner tank enclosed in steel weatherproof bund, with 110% capacity for the storage of fuel.

SPECIFICATION

Standard Tank Fittings: 2" Fill : 2" Vent Pipe with Valve : Pressure Vacuum Vent : 8 x 1½" Ports for Feed & Return Lines : Gauge : 2" Fitting for extra draw-off (optional) : Bolted Inspection Manhole : 4 x 3" Fusible Caps : 2 x Letterbox for Hose Feed			
Capacity Litres:	18500 (with overfill protection)	Inner Tank Thickness:	6mm (minimum)
Capacity (IMP) Gallons:	4070	Bund Material:	3mm (nominal)
Dimensions (mm):	L6058 x W2438 x H2438	Design Approvals:	As specified above
Weight ¹ Empty (Approx. kg)	5500	Design Standards:	ADR ch.6.7, UL142, COP Regulations, PPG2
Weight ¹ Full (Approx. kg)	21800		(Pollution Prevention Guidelines)

Notes

¹ Laden weight of container is based on diesel weight of 0.84 kg/litre. Capacity without overfill protection is 18500 litres.

Revision Date: 25/01/2016

